

3CP24 SmartProbe Stick Submittal



**Duplex Pump Down
Sequence On/All Off with High Alarm**

<p>CUSTOMER</p> <p>PO#</p> <p>SO#</p> <p>SHIP DATE</p> <p>QUANTITY</p> <p>WIRE LENGTH (ft)</p>	<p>SENSOR WIRE: Standard wire length is 20ft. Minimum wire length is 5ft. 18AWG Sensor Wire</p> <p>332 RED.....+VDC BLACK.....GND</p> <p>RELAY SWITCH WIRES: :7 <input type="checkbox"/>PUMP 1 21 <input type="checkbox"/>PUMP 2 GREEN...<input type="checkbox"/>...HIGH ALARM</p> <p>HTHQFHRI2SHUDWLRQ22 VODUPO <input type="checkbox"/> 1VNQ <input type="checkbox"/> 4UBSU IFOUIFBUEFSMEWFMDPOUBDUTUIE1VNQ4UBSUOH UIE#SPO3FMB4UDI0VUQVUSFHPETDUWE 1VNQ4UBSUIF#SPO3FMB4UDI0VUQVUSF SENBOTDUWFVUUMUIEUBFSMEWFEMGBMTCFMPUIE 114UPQSOH</p> <p>VODUPO <input type="checkbox"/> 1VNQ <input type="checkbox"/> 4UBSU IFOUIFBUEFSMEWFMDPOUBDUTUIE1VNQ4UBSUOH UIE#SPO3FMB4UDI0VUQVUSFHPETDUWE 1VNQ4UBSUIF#SPO3FMB4UDI0VUQVUSF SENBOTDUWFVUUMUIEUBFSMEWFEMGBMTCFMPUIE 114UPQSOH</p> <p>VODUPO <input type="checkbox"/> HIMBSN IFOUIFBUEFSMEWFMDPOUBDUTUIE)HIMBSNSOH UIE(SFEO3FMB4UDI0VUQVUSFMMCFODUWE)HIMBSN IFOUIFBUEFSMEWFEMTCFMPUIE)HIMBSNSOH UIE(SFEO3FMB4UDI0VUQVUSFMMCFODUWE</p> <p>Components PVC Slip Fitting cup. 1" Schedule 40 PVC Pipe with 3/4" passivated Stainless Steel rings (1" overall ring assembly). 18AWG Sensor Wire.</p> <p>Determining Ring Placement Measurement B is from the bottom of the ring to the bottom of the sensor stick. 3-1/2" minimum between rings. The Over All Length is measured from the bottom of the sensor cup to the bottom of the sensor stick.</p>
--	---

110/220 VAC Input

System Dynamics, Inc.
P.O. Box 12544
Scottsdale, Arizona 85260
Toll Free: 866-243-2505
sales@waterlevelcontrols.com
www.waterlevelcontrols.com

	(125	&20/(1#	
OAL			D + 9"
HIGH ALARM	<input type="checkbox"/>		
PUMP 2 START	<input type="checkbox"/>		
PUMP 1 START	&		
PUMP 1 & 2 STOP	<input type="checkbox"/>		
REFERENCE	<input type="checkbox"/>		3.5"

5/(25	,13	23	
RPB-12V-NO			
RPB-12V-NC			
RPB-24V-NO			
RPB-24V-NC			